



# PRODUCT DATA SHEET



---

## NO-TOX<sup>®</sup> FOOD GRADE PENETRATING LUBRICANT

**No-Tox Food Grade Penetrating Lubricant**, commonly known as No-Tox PL Plus Lubricant, is a low viscosity penetrating lubricant and is NSF H1 registered for use where incidental food contact may occur. It penetrates even the smallest of clearances to loosen seized parts.

**No-Tox Food Grade Penetrating Lubricant** cleans, lubricates and preserves, and is an excellent penetrating lubricant to be used in the “clean” industries such as food, beverage, pharmaceutical and personal care products.

### *Applications*

---

- ◆ Lubricates chains, bearings and many others
- ◆ Dissolves most gums and varnish
- ◆ Use as an all-purpose, once through machine oil

### *Features and Benefits*

---

- |                                |   |
|--------------------------------|---|
| ◆ NSF H1 registered            | Use where incidental food contact may occur.  |
| ◆ Compliance                   | Kosher and Pareve approved. Halal certified.  |
| ◆ Bacteriological protection   | Effectively inhibits the growth of certain bacteria, yeast and mold in the lubricant. |
| ◆ Penetrates                   | Frees frozen parts.   |
| ◆ Rust and oxidation inhibited | Protects metal surfaces.  |

### *General Description*

---

**No-Tox Food Grade Penetrating Lubricant** is a food grade penetrating oil. **No-Tox Food Grade Penetrating Lubricant** dissolves most gums and varnishes, frees immovable parts and prevents rust and corrosion. **No-Tox Food Grade Penetrating Lubricant**, formulated with the highest quality USP white mineral oils and food grade additives, meets NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified.

### *Product No. 301339*

# NO-TOX<sup>®</sup> PENETRATING LUBRICANT

## TYPICAL PROPERTIES

<b><u>Product No.</u></b>	<b><u>301339</u></b>
<b><u>Old Product No.</u></b>	<b><u>76000</u></b>
ISO Viscosity Grade	7
Viscosity, ASTM D445	
@ 40°C, cSt	7.20
@ 100°C, cSt	2.14
Viscosity, ASTM D2161	
@ 100°F, SUS	51.0
@ 210°F, SUS	33.4
Pour Point, ASTM D97	
°C	-34
(°F)	(-30)
Flash Point, ASTM D93	
°C	100
(°F)	(212)
Specific Gravity, ASTM D1298, 60/60°F	0.826
Density, ASTM D1298	
@ 60°F, lb/gal	6.89
Appearance	Clear
Color	Water-white